





	V	VA	RIVECO							O	V	A	A				
			E	O	O	E											
<b>Alternátory s AVR</b>																	
GP280 A/I-N	250	275	292	320	CURSOR 87 TE3 (E)	6	8700	45,2	51,1	150	3000	1100	2100	2200	/	M7	A5
GP280 SM/I-N			195	3800	1200	1930	3300	T87	M7	A5							
GP280 A/I			150	3000	1100	2100	2200	/	M7	A5							
GP280 SM/I			195	3800	1200	1930	3300	T87	M7	A5							
GP305 A/I	275	300	297	326	CURSOR 87 TE1D (E)	6	8700	47,6	54	150	3000	1100	2100	2400	/	M7	A5
GP305 SM/I										195	3800	1200	1930	3500	T87	M7	A5
GP330 A/I-N	300	330	358	390	CURSOR 87 TE4 (E)	6	8700	52,6	60,8	150	3000	1100	2100	2550	/	M7	A5
GP330 SM/I-N										195	3800	1200	1930	3900	T87	M7	A5
GP330 A/I	300	330	333	366	CURSOR 10 TE1D (E)	6	10300	53,7	63,8	290	3200	1300	2100	2550	/	M7	A5
GP330 SM/I										195	3800	1200	1930	3900	T87	M7	A5
GP385 A/I	350	385	385	423	CURSOR 13TE2A (E)	6	12880	57,3	67,4	290	3200	1300	2100	2850	/	M7	A5
GP385 S/I										230	3950	1300	2100	3750	T88	M7	A5
GP440 A/I	400	440	430	472	CURSOR 13TE3A (E)	6	12880	72,5	82,5	320	3400	1400	2200	2900	/	M7	A5
GP440 S/I										230	3950	1300	2100	3900	T88	M7	A5
GP505 A/I-N	450	495	475	540	C13 TE6W (E)	6	12880	72,5	81,6	320	3400	1400	2200	3130	/	M7	A5
GP505 S/I-N										410	4500	1450	2300	4340	T100	M7	A5
GP560 A/I-N	500	550	510	565	C13 TE7W (E)	6	12880	80,2	87,7	320	3400	1400	2200	3190	/	M7	A5
GP560 S/I-N										410	4500	1450	2300	4400	T100	M7	A5

A - bez kapoty

S - odhlu n á kapota, dve e otv írané do boku, panel na del í bo ní stran

SU - odhlu n á kapota, dve ŕe otv írané do boku, ane na krat í bo ní tran