



TYP	VÝKON kVA				MOTOR YANMAR					OBJEM NÁDRŽE L	ROZMĚRY			VÁHA kg	TYP KAPOTY	TYP PANELU	
	50 Hz		60 Hz		REGULÁTOR OTÁČEK (M) mechanický (E) elektronický	POČET VÁLCŮ	OBJEM VÁLCŮ ccm	SPOTŘEBA PALIVA			D mm	Š mm	V mm			MAN.	AUT.
	PRP	LTP	PRP	LTP				50 Hz	60 Hz								
Alternátory kompaundní																	
GP11 A/YW-C	8,7	9,5	10	11	3TNV76 (M)	3	1116	2	2,3	55	1300	700	1000	450	/	M1	A1
GP11SH/YW-C										70	1300	700	1020	510	T43	M1	A1
GP11 S/YW-C										70	1750	700	1100	580	T55	M1	A1
GP16 A/YW-C	13,5	15	15,4	16,8	3TNV88 (M)	3	1642	2,8	3,3	60	1500	700	1020	465	/	M2	A2
GP16 SH/YW-C										70	1750	700	1020	530	T45	M2	A2
GP16 S/YW-C										70	1750	700	1100	610	T55	M2	A2
GP22A/YW-C	19	21	20,6	22,7	4TNV88 (M)	4	2190	3,7	4,4	60	1500	700	1020	500	/	M2	A2
GP22SH/YW-C										70	1750	700	1020	590	T45	M2	A2
GP22S/YW-C										70	1750	700	1100	690	T55	M2	A2
Alternátory s AVR																	
GP22A/YW	19	21	20,6	22,7	4TNV88 (M)	4	2190	3,7	4,4	60	1500	700	1020	530	/	M2	A2
GP22SH/YW										70	1750	700	1020	600	T45	M2	A2
GP22S/YW										70	1750	700	1100	700	T55	M2	A2
GP33A/Y	30	33	35	39	4TNV98 (M)	4	3319	5,2	5,2	70	1750	700	1100	640	/	M4	A3
GP33S/Y										100	2100	900	1150	865	T60	M4	A3
GP44A/Y	42	46,2	46	50	4TNV98T (M)	4	3319	7	7	70	1750	700	1100	730	/	M4	A3
GP44S/Y										100	2100	900	1150	960	T60	M4	A3